

Product Data

DFR 1275

Paper Machine Defoamer

DESCRIPTION:

DFR 1275 is an economical and effective water-based defoamer designed for use in a variety of industrial applications. It has found use in screen room operations, effluent treatment and paper making process. It is effective over a wide pH range and temperature. It is free of mineral oil.

TYPICAL PROPERTIES:

Appearance	White Emulsion
Density @ 28 °C	0.960 ± 0.02 gr/lit
Ionic Nature	Non-ionic
Viscosity @ 28 °C	70 – 1000
% Solids	24 – 26 %
pH @ 28°C	7.0 – 11

FDA:

The components of this product comply with the regulations of the FDA as cited in 21 CFR 176.210.

USAGE:

DFR 1275 can be added neat as received or it can be diluted with water to form a transiently stable emulsion. **DFR 1275** should be added to the substrate at a suitable point where intimate mixing occurs. Addition levels vary with foaming conditions and the type of process streams being treated. Typical dosages range from 100-1000 ppm.

HEALTH AND SAFETY:

Avoid contact with skin, eyes and clothing. Avoid breathing any vapors and do not take internally.

Store the product in a relatively cool, dry place. Storage in stainless steel, plastic or epoxy lined containers is recommended.

EMERGENCY AND FIRST AID PROCEDURE:

Eyes: Flush with large amount of water for at least 15 minutes.

Skin: Wash with soap and water.

Inhalation: Remove to fresh air.

Ingestion: Do not induce vomiting. Give large amount of water. Seek medical aid.

PACKAGING:

DFR 1275 is packed in tote bin of 1000 kgs. net or in plastic drum of 200 kgs. net.

Office / Factory :

Jl. Raya Sumput No. 17, Driyorejo – Gresik, East Java _ Indonesia
Telp. (031) 7507156 Fax : (031) 7507400
Email : info@indopicri.net