

Product Data

INDOCLEAN AC

Acid Based Cleaning Agent

DESCRIPTION :

INDOCLEAN AC can be used without any problems as a Universal Cleaner, e.g. for removal of mainly inorganic deposits on wire, felt, roll, suction box cover, foils, frame, machine parts, etc.

The combination of acid components and surfactant ensure an excellent cleaning effect especially in case of carbonate-containing contamination.

INDOCLEAN AC is also used for acid treatment of felts due to its gentle properties.

SPECIAL INFORMATION

- Maximum reaction time : 15 minutes
- The application devices used for the cleaning must be washed immediately and thoroughly after use.
- It is imperative to adhere to the precautionary measures that are necessary when handling sulphuric acid.

PHYSICAL AND CHEMICALS PROPERTIES

Form	Liquid-colourless yellow
Odour	Slight stinging
Chemical characteristic	Acidic foaming solution of surfactant
PH (at 20°C)	< 2
Density (at 20°C)	1.06 ± 0.02 gr/lit
Viscosity (at 25°C)	< 10 mPa.s

RECOMMENDATION FOR APPLICATION

INDOCLEAN AC has to be applied undiluted, e.g. by means of foam unit or via spray pipe or locally by pouring on, etc. The dosage depends on the contamination of the item to be clean.

Office / Factory :

Jl. Raya Sumpat No. 17, Driyorejo – Gresik, East Java _ Indonesia
Telp. (031) 7507156 Fax : (031) 7507400
Email : info@indopicri.net