

## Product Data

### INDOCLEAN BS

*Boil Out/Circuit System Cleaning*

#### DESCRIPTION :

**INDOCLEAN BS** can be used without any problem as circuit cleaning for removal of organic deposits, chest, headboxes, screens, etc.

**INDOCLEAN BS** reaches all usually inaccessible parts of the systems and so detaches all organic contamination completely. If regular chemical circuit cleaning is carried out with **INDOCLEAN BS**, the application of biocide can be reduced.

#### PHYSICAL AND CHEMICAL PROPERTIES :

Form	Fluid
Smell	Characteristic
Chemical characteristic	Mixture of nonionic surfactant and solvent in aqueous solution
Solubility	100 %
pH at 20°C	11- 13
Density at 20°C	1.0 ± 0.015 gr/cm <sup>3</sup>
Viscosity	< 50 cps

#### SPECIAL INFORMATION :

- Best possible results are achieved with a long circuit cleaning (approx. 2 – 4 hours)
- Ideal cleaning temperatures are between 55 – 60 °C (every increase in temperature of 10 °C will cut in half the required time for cleaning)
- It is imperative to adhere to precautionary measures that are necessary when handling caustic soda.

#### RECOMMENDATION FOR APPLICATION :

- **INDOCLEAN BS** is added in alkaline solution, (add caustic soda until pH value 11 – 12)
- Approximate level of consumption : 1 – 1.5 kg/m<sup>3</sup>

#### Office / Factory :

Jl. Raya Sumput No. 17, Driyorejo – Gresik, East Java \_ Indonesia  
 Telp. (031) 7507156 Fax : (031) 7507400  
 Email : info@indopicri.net