

INDOCLEAN DF

Dryer Canvas Cleaning

DESCRIPTION :

INDOCLEAN DF is applied – in the first place – for **cleaning of dryer fabrics**. Immediately after application **INDOCLEAN DF** penetrates the hollows between dryer fabric surface and dirt particle and breaks up the adhesive strength between the two **(Penetration)**

Thereby the surface-active additives ensure a rapid wetting and the solvents prevent a re-deposit, so that the dirt can be washed off without any problem **(Cleaning)**.

Moreover, a special component surrounds the dryer fabric fibres and spreads a kind of protective film which has a repellent effect on dirt particles and thus, as a rule, delays resoiling considerably **(Conditioning)**. The physical properties of the dryer fabric are preserved. **INDOCLEAN DF** cleans and conditions in one single operation.

SPECIAL INFORMATION

- For dryer fabric cleaning we suggest a dilution of 1: 1 to 1: 4
- Maximum reaction time: 15 minutes

PHYSICAL AND CHEMICAL PROPERTIES :

Form	Liquid
Odor	Aromatic
Chemical Characteristic	Mixture of hydrocarbons, surfactants and caustic
pH (at 20 ° C)	± 13
Density (at 20°C)	0.98 ± 0.015 gr/lit

RECOMMENDATION FOR APPLICATION :

INDOCLEAN DF is applied diluted or undiluted, e.g. by means of foam unit or via spray pipe or locally by pouring on. The dosage depends on the contamination level of the item to be cleaned.

Approximate consumption : 1 - 1.5 kg/m²

Office / Factory :

Jl. Raya Sumpat No. 17, Driyorejo – Gresik, East Java _ Indonesia
 Telp. (031) 7507156 Fax : (031) 7507400
 Email : info@indopicri.net