

### INDOCLEAN SR

Surfactant

#### DESCRIPTION :

**INDOCLEAN SR** is used as a neutral cleaning and conditioning agent for general purpose, e.g. for felt, wires, circuit, frames, rolls, machine parts, etc.

**INDOCLEAN SR** is a nonionic, neutral cleaner which has not only an excellent cleaning but also dirt-repelling effect.

**INDOCLEAN SR** forms a monomolecular protective film, e.g. on the surface of each felt fiber, and thus lime, bitumen, size, resin, etc. will no longer deposit, harden or crystallize. The special merits of **INDOCLEAN SR** are outstanding penetration properties.

#### PHYSICAL AND CHEMICAL PROPERTIES :

Form	Fluid
Smell	Characteristic
Chemical characteristic	Mixture of nonionic surfactant in aqueous solution
Solubility	100 %
pH at 20°C	7 - 8
Density at 20°C	1.03 ± 0.01 gr/cm <sup>3</sup>
Viscosity	< 30 mPas

#### RECOMMENDATION FOR APPLICATION :

- **Felt Cleaning During Production**  
Addition in concentrated form into a suitable washing spray pipe by means of a metering pump. Production Consumption per liter fresh water :  
0.1 – 0.2 gr/lit

- **Felt And General Cleaning At Machine Stop**

Prepare a 10% washing solution. Application by means of a foam unit or drum pump via spray pipe or locally pouring on, etc.

- **As Circuit Cleaning Additive**

Product consumption: 1 – 1.5 kg/m<sup>3</sup> chest capacity.

#### SPECIAL INFORMATION :

**Hint:** In case of prolonged machine stops we recommend Felt Conservations, i.e. application of a 10 – 20% **INDOCLEAN SR** solution. Advantage: the felt remain evenly soft and allow an unproblematic re-start of the machines. Prior to start up the felts must be rinsed thoroughly. **INDOCLEAN SR** is also extremely suitable as a surfactant additive for self-made washing solutions (caustic soda, hydrochloric or sulphuric acid, etc.)

#### Office / Factory :

Jl. Raya Sumput No. 17, Driyorejo – Gresik, East Java \_ Indonesia  
Telp. (031) 7507156 Fax : (031) 7507400  
Email : [info@indopicri.net](mailto:info@indopicri.net)