

INDOFIX*Wire Conditioning Agent***DESCRIPTION :**

INDOFIX is used for wire conditioning. By using **INDOFIX** during waste paper processing or when applying wet-strength agents, the deposits on wires are reduced considerably. Consequently, far less cleaning during machine stop is necessary. **INDOFIX** adsorbs at the fabric surface and so gives the wire a dirt-repelling character. This has no adverse effect on the drainage capacity. **INDOFIX** prevents deposit build up on the wire and minimizes the shutdown cleaning time.

PHYSICAL AND CHEMICAL PROPERTIES

Form	Liquid
Color	Slightly opaque
Chemical Characteristic	Methylene bridged, polyquaternary Ammonium salt
Total Solid, %	22 – 24 %
pH (conc.)	3 - 4
Density at 25 ° C	1.045 – 1.065 gr / cm ³
Water solubility	100 %

SPECIAL INFORMATION

- In order to achieve an even distribution, traversing low-pressure spray pipes should be used.
- In case of overdosing, the wire may get a brownish color, which does not – as a rule – affect the drainage.
- The color can be removed easily with alkaline foam cleaner.
- **INDOFIX** is sensitive to frost and should be stored above freezing.

RECOMMENDATION FOR APPLICATION

INDOFIX is diluted with water and applied continuously onto the wire just before breast roll.

Dosage :

Waste paper : 5 - 10 ml/min/meter per width of wire

Wet strength : 10 - 25 ml/min/ meter per width of wire

Office / Factory :

Jl. Raya Sumpat No. 17, Driyorejo – Gresik, East Java _ Indonesia
Telp. (031) 7507156 Fax : (031) 7507400
Email : info@indopicri.net