

INDOFIX 11C

Conditioning Agent

DESCRIPTION :

INDOFIX 11C is a conditioning agent for guide roll at press and dryer section. By using **INDOFIX 11C** during waste paper processing or when applying wet-strength agents, the deposits on wires are reduced considerably. Consequently, far less cleaning during machine stop is necessary.

INDOFIX 11C adsorbs at the surface roll and so gives the a dirt-repelling character. This has no adverse effect on the drainage capacity.

INDOFIX 11C prevents deposit build up on the wire and minimizes the shutdown cleaning time.

PHYSICAL AND CHEMICAL PROPERTIES

Form	Liquid
Color	Slightly opaque
Chemical Characteristic	Polyquaternary Ammonium salt
Total Solid, %	22 – 24 %
pH (conc.)	3 - 4
Density at 25 ° C	1.05 ± 0.055 gr / lt
Water solubility	100 %

RECOMMENDATION FOR APPLICATION

INDOFIX 11C is diluted with water and applied continuously onto the wire just before breast roll.

Dosage :

Waste paper : 5 - 10 ml/min/meter per width of machine roll.

Wet strength : 10 - 25 ml/min/ meter per width of machine roll

Office / Factory :

Jl. Raya Sumpat No. 17, Driyorejo – Gresik, East Java _ Indonesia
Telp. (031) 7507156 Fax : (031) 7507400
Email : info@indopicri.net

SPECIAL INFORMATION

- In order to achieve an even distribution, traversing low-pressure spray pipes should be used.
- In case of overdosing, the wire may get a brownish color, which does not – as a rule – affect the drainage.
- The color can be removed easily with alkaline foam cleaner.
- **INDOFIX 11C** is sensitive to frost and should be stored above freezing.