



PT. INDOPICRI

Jl. Raya Sumpat No. 17 Driyorejo 61177
Tel. +62 31 7507156 (Hunting), Fax. +62 31 7507400
Gresik – East Java – INDONESIA
E-mail : info@indopicri.net

Technical Data Sheet

IPC_RESIN IGR-085

DESCRIPTION

IPC_RESIN IGR-085 is a glycerol rosin ester resin with moderate acid number. This resin designed for use as a tackifier in adhesive, ink and paint with exhibit good tack, gloss and compatibility.

APPLICATIONS

As a tackifier in adhesive, ink and paint application where good tack, gloss and stability are required.

FEATURES

- Soluble in aromatic and aliphatic hydrocarbon solvents.
- Compatible with SBR, natural rubber, chlorinated rubber, neoprene, acrylic polymers, EVA copolymer, hydrocarbon resins and alkyd resins.

PACKAGING

Polypropylene woven bag 25 kg net.

STORAGE

Product should be stored under cover, dry condition, in a clean and well ventilated area. Keep away from heat, sparks and other sources of ignition. No smoking. It is recommended that it be used on a first-in first-out basis.

TECHNICAL DATA

Description	Specification
Appearance	Lump and Granule
Viscosity, Gardner, 70% in Toluene	U – W
Acid Value, mgKOH/g, max.	40
Color, Gardner, max.	5
Melting Point, °C, R&B	85 ± 5

The information herein is given in good faith and believed to be reliable, but is not to be as a warranty for legal responsibility. Users should undertake sufficient verification and testing for their own particular purpose of any information or products referred to herein.